

NEW!

Pure-Fit™ SC

True Sterile Connections Outside the Clean RoomSM




Introducing connective technology that makes completely sterile connections possible *outside* the clean room environment.

Features/Benefits:


- Silicone valve design is easy to assemble — leaves no gaps or residue, eliminating problems associated with other systems
- Use of Pure-Fit® SIB® patented technology on barb connections ensures a completely smooth inner bore flow path
- Available in three common sizes (1/4", 3/8", 1/2") that are fully interchangeable for step-down requirements
- All components made of fully characterized, animal-free materials
- Triple-redundant locking mechanism simplifies validation, virtually eliminating chances of operator error
- Easy-to-see visual indicators confirm proper engagement
- Can be sterilized via gamma irradiation or autoclaving

Inner Housing Assembly



Outer Housing Assembly

Pure-Fit® SIB® Connective Technology



Pure-Fit® SIB® Connective Technology

sani-tech west

321 Irving Drive
Oxnard, CA 93030
(800) 726-4835
www.sani-techwest.com


NEW!

Pure-Fit™ SC

Assembly Sequence for Pure-Fit® SC Connection

The assembly starts after the barbed ends have been connected to your product.

1. Remove the Inner Housing and Outer Housing Safety Caps.
2. Attach the Tubing and Retainers to the Pure-Fit® SIB Barbed ends.
3. Pull up the Tear Tabs, then remove the Protective Caps.
4. Insert the Inner Housing into the Outer Housing; note lock size versus slot size.
5. Rotate the Inner Housing inside the Outer Housing to line up locks.
6. Fully insert Inner Housing locks into locking track window.
7. After insertion, rotate the Inner Housing clockwise in the Outer Housing until it locks.
8. Fully depress the Locking Clip against Inner Housing with your thumb.
9. Push the Inner Fitting into the Inner Housing until it stops.
10. Grasp the end of the Inner Fitting and rotate it clockwise until it locks.



The sanitary connection is complete and fluid can flow through the connection.

sani-tech west

321 Irving Drive
Oxnard, CA 93030
(800) 726-4835
www.sani-techwest.com



Pure-Fit™ SC

Specifications & Ordering Information

Materials of Construction

Inner Housing (a)	PVDF
Outer Housing (a)	PVDF
Inner Fitting	PVDF
Valve	Platinum-Cured Silicone
Valve Retainer	PVDF
O-Ring	Platinum-Cured Silicone
Locking Clip	PVDF
Protective Cap	C-Flex®
Safety Cap	Polypropylene

(a) Fluid Contact Path

Note: All materials of construction are animal derivative-free.

Operating Conditions

Maximum Operating Pressure	psi (bar)
Series 250 (1/4")	50 (3.45)
Series 375 (3/8")	50 (3.45)
Series 500 (1/2")	50 (3.45)
Operating Temperature °F (°C)	32 (0) to 104 (40)
Storage Temperature °F (°C)	-40 (-40) to 77 (171)

Sterilization Methods

Gamma Irradiation	50 kGy
Autoclave	134C, 60 Minutes

Typical Flow Rate Data

Series Number	Assembled Connector Length inches (mm)	Typical Maximum Flow Rate (Bi-directional)
		Gallons (Liters) / Minute
250	5.72 (145.29)	7.41 (28.04)
375	6.06 (153.92)	8.80 (33.32)
500	6.17 (156.72)	10.61 (40.18)

Note: Flow rates were tested under 9 psi of operating pressure.

Available Pure-Fit® SC Characterization Data

- Biological Test Protocols
- Chemical Test Protocols
- Physical and Functional Test Data
- Microbial Barrier Test Protocols
- Helium Leak Test Data
- Sterilization Test Information

Pure-Fit® SC Selection Guide

Part Number	Configuration	Hose Barb inches (mm)	Length inches (mm)	Width inches (mm)	Quantity
PFSC250-CA	Complete Assembly Set	1/4 (6.35)	5.72 (145.29)	1.58 (40.13)	1 set per box
PFSC250-IH	Inner Housing	1/4 (6.35)	4.23 (107.44)	1.48 (37.59)	25 per box
PFSC250-OH	Outer Housing	1/4 (6.35)	2.00 (50.80)	1.58 (40.13)	25 per box
PFSC375-CA	Complete Assembly Set	3/8 (9.53)	6.06 (153.92)	1.58 (40.13)	1 set per box
PFSC375-IH	Inner Housing	3/8 (9.53)	4.48 (113.79)	1.58 (40.13)	25 per box
PFSC375-OH	Outer Housing	3/8 (9.53)	2.11 (53.59)	1.58 (40.13)	25 per box
PFSC500-CA	Complete Assembly Set	1/2 (12.70)	6.17 (156.72)	1.65 (41.91)	1 set per box
PFSC500-IH	Inner Housing	1/2 (12.70)	4.56 (115.82)	1.65 (41.91)	25 per box
PFSC500-OH	Outer Housing	1/2 (12.70)	2.14 (54.36)	1.58 (40.13)	25 per box

Note: All parts are supplied double bagged and non-sterile.

Inner and outer housings are completely interchangeable for step-down requirements.

C-Flex®, S.I.B.® and Pure-Fit® are registered trademarks of Saint-Gobain Performance Plastics, inc.



321 Irving Drive
 Oxnard, CA 93030
 (800) 726-4835
 www.sani-techwest.com